

**AMENDMENTS TO THE CLAIMS**

1. (Original) An information handling system (IHS) comprising:
  - a system board including a processor;
  - a first battery for supplying power to the system board;
  - a second battery for supplying power to the system board; and
  - a switching circuit coupled to the first battery, the second battery and the system board, for repeatedly switching between the first battery and the second battery for supplying power to the system board.
2. (Original) The IHS of claim 1, wherein the switching circuit connects the first battery to supply power to the system board during first periods of time alternating with second periods of time during which the switching circuit connects the second battery to supply power to the system board.
3. (Original) The IHS of claim 2, wherein the peak power that can be drawn from the first battery during the first time periods is greater than the power that the first battery is capable supplying under a continuous load.
4. (Original) The IHS of claim 2, wherein the peak power that can be drawn from the second battery during the second time periods is greater than the power that the second battery is capable of supplying under a continuous load.
5. (Original) The IHS of claim 2, wherein the first time periods are equal in duration to the second time periods.
6. (Original) The IHS of claim 2, wherein the first time periods are greater in duration than the second time periods.

7. (Original) The IHS of claim 2, wherein the first time periods are shorter in duration than the second time periods.
8. (Original) The IHS of claim 1, wherein the switching circuit includes a field effect transistor (FET) switch.
9. (Original) The IHS of claim 8, wherein the FET switch operates in response to a switching signal generator.
10. (Original) The IHS of claim 9, wherein the switching signal generator exhibits a variable switching frequency.
11. (Original) The IHS of claim 1, further comprising a capacitor coupled to the switching circuit, wherein the capacitor is for stabilizing the voltage supplied to the system board.
12. (Original) The IHS of claim 1 wherein the IHS is a portable IHS.
13. (Original) A method of operating an information handling system (IHS) comprising:
  - supplying power from first and second batteries to a battery switching circuit; and
  - repeatedly switching, by the battery switching circuit, between a first battery and a second battery for supplying power to the IHS.
14. (Original) The method of claim 13, wherein switching comprises connecting, by the switching circuit, the first battery to supply power to the system board during first periods of time alternating with second periods of time during which the switching circuit connects the second battery to supply power to the system board.

15. (Original) The method of claim 14, wherein the peak power that can be drawn from the first battery during the first time periods is greater than the power that the first battery is capable of supplying under a continuous load.
16. (Original) The method of claim 14, wherein the peak power that can be drawn from the second battery during the second time periods is greater than the power that the second battery is capable supplying under a continuous load.
17. (Original) The method of claim 14, wherein the first time periods are equal in duration to the second time periods.
18. (Original) The method of claim 14, wherein the first time periods are greater in duration than the second time periods.
19. (Original) The method of claim 14, wherein the first time periods are shorter in duration than the second time periods.
20. (Original) The methods of claim 13, wherein the switching circuit includes a field effect transistor (FET) switch.
21. (Original) The method of claim 20, wherein the FET switch operates in response to a switching signal generator.
22. (Original) The method of claim 21, wherein the switching signal generator exhibits a variable switching frequency.
23. (Original) The method of claim 13, further comprising stabilizing, by a capacitor, the voltage supplied to the system board.

24. (New) A method of operating an information handling system (IHS) comprising:
- providing a system board including a processor;
  - supplying power to the system board by means of a first battery and a second battery;
  - coupling a switching circuit to the first battery, the second battery and the system board; and
  - repeatedly switching, by the battery switching circuit, between the first battery and the second battery for supplying power to the IHS.